




<b>DESCRIPTION</b>			
Total thickness	EN 428	mm	2.00
Weight	EN 426	g/m <sup>2</sup>	3300
Width of sheet	EN 426	cm	200
Length of sheet	EN 427	lm	20
Tile size	EN 427	mm	608 x 608
Number of tiles per package	EN 428	-	20
<b>CLASSIFICATION</b>			
Standard / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
Fire rating	EN 13501-1	class	B <sub>fl</sub> -s1
Electrical resistance	EN 1081	Ohm	10 <sup>6</sup> ≤ Rt ≤ 10 <sup>8</sup>
	IEC 61340-5-1	Ohm	10 <sup>6</sup> ≤ Rt ≤ 10 <sup>9</sup> *
	ANSI / ESD-S7.1	Ohm	10 <sup>6</sup> ≤ Rt ≤ 10 <sup>8</sup>
Static electrical propensity	EN 1815	kV	< 2
	IEC 61340 -4-5	V	< 100
<b>PERFORMANCE</b>			
Wear resistance	EN 660.2	mm <sup>3</sup>	≤ 7.5
Wear group	EN 649	-	M
Type Binder content	ISO 10581	type	II
Dimensional stability	EN 434	%	sheet ≤ 0.40 tile ≤ 0.25
Residual indentation	EN 433	mm	~ 0,03
Castor chair test (type W)	EN 425	-	OK
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	-	OK
<b>ENVIRONMENT / INDOOR AIR QUALITY</b>			
TVOC after 28 days	ISO 16000-6	µg/ m <sup>3</sup>	< 10
<b>CE MARKING</b>			
	EN 14041	-	
		-	

\* Not compliant with IEC 61340-5-1 layed on raised floor