

SPECIFICATION OF BKB HEVEA PRODUCTS**Product: 3 – PLY ENGINEERED WOOD FLOORING****Specification: Full Plank, 2 strip, 3 strip and Fineline**

Thickness – BKB Parquet	14.0mm +/- 0.5mm	
Thickness of top layer	3.5mm +/- 0.5mm	
Thickness of middle layer (core strip)	8.8mm +/- 0.2mm	
Thickness of bottom layer (veneer)	2.0mm +/- 0.1mm	
Surface layer length (panel)	2190 mm +0/-20mm 1830mm +0/-20mm	
Surface layer width (panel)	190mm /180mm / 138mm / 125mm +/- 0.1mm	
Finishing	Treated with water based Primer + 6 coats of UV Acrylic – 80gm/m ²	
Weight/pack	~ 20 kg (6pieces/pack)	
Gloss level of surface layer	25 +/- 5%	
Properties	Declaration according to EN 13432	
1. Fire resistance according to EN 13501-1	D _{fl} S1 classified according to EN 1350-1	
2. Formaldehyde emission according to EN 717-1	Class E1	
3. Anti skid properties according to EN 1339	USRV 15 and USRV 20	
Recommended maintenance	As per BKB's Maintenance programme	
Opening between panels (when laid)	According to DIN EN 13489	
Surface layer composition	1 Strip	1 lamella
	2 Strip	2 + 2; 2 + 3 and 3 + 3
	3 Strip	Random pattern
Nested layers	2 and 3 strips	1 layer
	Full plank	2 layers
	Full plank – Cherry and Walnut	3 layers
Height difference between panels	0.2 mm (max)	
Moisture content	7 +/- 1%	
Width of lamella	63.34 mm	
Recognized certification	MS ISO 9001– 2000, FSC, WWF, MTCC, F4 Star Ministerial Approval	
Oil	Trip Trap Industrial oil / Monocoate (Stone/Beton)	
Varnish	UV Acrylic/Water based/PU - Bona	
Glue	Urea Formaldehyde E1 class – Dynea OR EPI Formaldehyde-free Glue	