

# SERIE 2 250



deZign FLOOR  
*the art of vinyl*



LVT Glue Down



SUBJECT	MAIN PARAMETER	REFERENCE
<b>GENERAL INFORMATION</b>		
Thickness	2,5mm	
Wear Layer	0,55mm	
Packaging Unit	12pieces/box = 3,34m <sup>2</sup>	
Plank Size	228,6 x 1219,2 x 2,5mm	
Application	Medium commercial	
Guarantee	20 year limited residential / 5 year limited commercial	
<b>TECHNICAL DATA</b>		
Name	Regular Emboss (2,5mm/0,55mm)	
Type of flooring	Heterogeneous PVC floor covering	ISO 10582
Classification	32	ISO 10874
Component	PVC plasticizer Stabilizer CaCO <sub>3</sub>	
Structure	Composite (Wear Layer: 0,55mm; Print film: 0,07mm; Back Layer: 1,88mm)	
Size	Deviation ≤0,15% of nominal length up to 0,5mm maximum	ISO 24342
Squareness, mm	≤400mm deviation≤0,25; >400mm, ≤0,35>400mm, ≤0,35	ISO 24342
Straightness, mm	≤400mm deviation≤0,25; >400mm, ≤0,35>400mm, ≤0,35	ISO 24342
Overall thickness, mm	Average: 2,5mm + 0,13/-0,10mm, individual value: average +/- 0,15mm	ISO 24346
Wear layer thickness, mm	0,55mm +13%/ -10%	ISO 20340
Surface treatment	PU coating	
Bevelled edges	mV4	
Colour Fastness	Minimum 6	ISO 105-B02
Dimensional Stability	≤0,25%	ISO 23999
Total Mass Per Unit Area	4,286 kg/m <sup>2</sup> + 13%/-10%	ISO 23997
Residual Indentation (average)	≤0,10 mm	ISO 24343-1
Reaction to fire	Bfl-s1	EN 13501-1
Chemical resistance	Class 0, excellent	ISO 26987
Effect of a castor chair	25 000 cycle no delamination	ISO 4918
Slip Resistance	≥R9	DIN 51130
	DS	EN 13893
Hardness	60°+/-5°	
Abrasion Resistance	Group T	EN660-2
Toxicity	Non-toxic, does not contain heavy metals	EN71-3
Formaldehyde Emission	E1	EN 717-1
Recycled Materials	No	
<b>INSTALLATION &amp; MAINTENANCE GUIDELINES</b>		
Caution	Do not expose to direct sunlight	
Installation	Adhere to manufactures installation parameters	
Cleaning & Maintenance	Non-abrasive detergent & micro fibre mop	
	Avoid excessive exposure to water	